












LED SPOTLIGHT

L00116



-  IP65
-  CLASS III
-  Surface Mounted Installation
-  ECO Energy Saving
-  Flicker Free
-  Eyes friendly CE certificate RoHS standard
-  CRI 90+ OSRAM SMD LED
-  Europe Standard & CE Certificate. DC12-24V.
-  400-600mm cable with quick connector
-  DALI I Triac I 0/1-10V dimmable

An ideal accent lighting in residential or commercial places



Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L00116 -3	3W	190lm	Ø 25xH64mm	Ø mm	500mA

FEATURES

The IP65 lighting fixture matched 80° adjustable and 355°rotatable, suitable for light up anywhere. Lens version, 30° output for a better visual comfort. Osram branded LED. High CRI. Aluminium materials - black color finishing as standard. On the request it can be offered in any RAL colour, matching the specific look and feel of your design. Matched main dimming and Dali dimming. Surface mounted installation as standard. Insert into the ground or recessed installation can be customized. 50000hours life time. DC12-24V.

Remote LED Driver Accessoires

3W 500mA

Beam Angle



Color Temperature

-  2700K
-  3000K
-  4000K
-  5000K
-  6000K

Finishes

-  Black
-  White
-  Customized