








INTERIOR LED RECESSED DOWN SPOTLIGHT

L01002



-  IP20
-  CLASS III
-  Europe Standard & CE Certificate. 220-240V 50/60Hz
-  Aluminium electroplating lighting fixture
-  Ceiling recessed, Ceiling thickness 3-25mm
-  400-600mm cable with quick connector
-  OSRAM LED 3535
-  Flicker Free, Remote LED Driver version. High PF
-  UGR <16 Deeply recessed light source. High level of visual comfort
-  0/1-10V | Triac | DALI dimming

HIGH LEVEL OF VISUAL COMFORT AND UNIFORM DISTRIBUTION



Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L01002 -2	2W	90lm	Ø 32xH50mm	Ø 25mm	700mA
L01002 -3	3W	160lm	Ø 50xH30mm	Ø 35mm	700mA

FEATURES

Fixed spotlight with trim, visual comfort low glare optic with recessed light source. Uniform distribution and soft light. Spring for easy installation. Easy to highlight the beauty. Create your customized light atmosphere. Easy lighting demand, for a wide scala of projects, from residential to hotels, restaurants, retail and much more. Customized color finishing, power changes are possible depending on the request and the quantity.

Remote LED Driver






- 2W 700mA
- 3W 700mA

Accessoires

Beam Angle



Color Temperature

-  2700K
-  3000K
-  4000K
-  5000K
-  6000K

Finishes

-  Black
-  White
- Customized