












## INTERIOR LED RECESSED DOWN SPOTLIGHT

L03250



-  IP54
-  CLASS III
-  Europe Standard & CE Certificate. 220-240V 50/60Hz
-  Aluminium die casting and powder coating.
-  Ceiling recessed, Trimless Square
-  5years Warranty
-  CREE COB LED 3SDCM CRI90
-  Flicker Free, Remote LED Driver version.
-  Deeply recessed light source. Visual comfort.
-  DALI Dimming from 0~100%, down to 0.01%.

### UNIFORM DISTRIBUTION AND SOFT LIGHT



Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L03250 -7	7W	560lm	□ 130x130xH75mm	□ 80x80mm	150mA
L03250 -15	15W	1050lm	□ 130x130xH95mm	□ 80x80mm	350mA
L03250 -18	18W	1260lm	□ 130x130xH105mm	□ 80x80mm	450mA

## FEATURES

Luminaires in this line have modular design. They comprise a LED light module, a metal baffle and a metal mounting frame. One housing achieved multiple options and different light distributions for a wide variety of applications, the new creating that meets the needs of your residential and commercial projects. The spotlight offer homogeneous and uniform light distribution. deep cut-off angle 45°. easy installations. deeply recessed light source. High Definition optical lenses in thermoplastic material. Specialized optics and optical filters can be ordered. 5years warranty. Flicker-Free. Dimmable. Customized color finishing, power changes are possible depending on the request and the quantity. Moreover, IP54 means that they can be used even in bathroom or other damp indoor locations. This enables you to continue the ceiling uniformity throughout bathrooms, wellness areas and other indoor damp locations.





#### Remote LED Driver

7W 150mA  
15W 350mA  
18W 450mA






#### Accessoires



#### Beam Angle

-  15°
-  24°
-  36°
-  55°

#### Color Temperature

-  2700K
-  3000K
-  4000K
-  5000K
-  6000K

#### Finishes

-  Black
-  White
-  Customized