












INTERIOR LED SURFACE MOUNTED SPOTLIGHT

L03254



-  IP20
-  CLASS III
-  Surface Mounted
-  Aluminium lighting fixture, powder coated.
-  Flicker Free
-  Eyes friendly CE certificate RoHS standard
-  CRI90+ 3SDCM CREE COB LED
-  DALI Triac I 0/1-10V I DALI dimmable
-  300-400mm cable with quick connector.
-  Warranty 5 Years

HIGH LUMINOUS EFFICIENCY AND UNIFORM DISTRIBUTION.



Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L03254 -36	36W	3600lm	Ø 90xH235mm	Ø mm	900mA
L03254 -40	40W	4000lm	Ø 90xH235mm	Ø mm	1000mA

FEATURES

The spotlight achieved 90°adjustable 355°rotation, The high performances and flexibility for every project. High Definition optical lenses in thermoplastic material. - The surface mounted luminaire with a decorative metal baffle. The new lens optic creates homogeneous lighting Uniform distribution. An ideal solution for accent lighting in residential or commercial. The basic model comes in white and black colors. Specialised optical filters can be ordered. Customized the color finishing of body and baffle or length of tube are possible depending on the request and the quantity. White OR Black color finishing as standard. --Customized power changes are possible depending on the request and the quantity. -On the request it can be offered in any RAL colour, matching the specific look and feel of your design.

Built in LED driver

36W 900mA
40W 1000mA

Accessoires



Beam Angle

-  15°
-  24°
-  38°
-  55°

Color Temperature

-  2700K
-  3000K
-  4000K
-  5000K
-  6000K

Finishes

-  Black
-  White
- Customized