














INTERIOR LED SURFACE MOUNTED SPOTLIGHT

L08620



-  IP44
-  CLASS III
-  Surface Mounted
-  Aluminium lighting fixture, powder coated.
-  Flicker Free
-  Eyes friendly CE certificate RoHS standard
-  CRI >97
-  DALI Triac I 0/1-10V I DALI dimmable
-  300-400mm cable with quick connector.
-  Warranty 5 Years

HIGH LUMINOUS EFFICIENCY AND UNIFORM DISTRIBUTION.



Code	System Power W	Output Lumen lm	Dimension mm	Cut Hole mm	Power Supply mA
L08620 -10	10W	900lm	Ø 40xH139mm	Ø mm	250mA
L08620 -15	15W	1300lm	Ø 52xH168mm	Ø mm	350mA
L08620 -20	20W	1700lm	Ø 63xH190mm	Ø mm	500mA

FEATURES

The spotlight achieved 90°adjustable 355°rotation, The high performances and flexibility for every project. High Definition optical lenses in thermoplastic material. - The surface mounted luminaire with a decorative metal baffle. The new lens optic creates homogeneous lighting Uniform distribution. An ideal solution for accent lighting in residential or commercial. The basic model comes in white and black colors. Specialised optical filters can be ordered. Customized the color finishing of body and baffle or length of tube are possible depending on the request and the quantity. White OR Black color finishing as standard. --Customized power changes are possible depending on the request and the quantity. -On the request it can be offered in any RAL colour, matching the specific look and feel of your design.



Built in LED driver

10W 250mA
15W 350mA
20W 500mA

Accessoires



Beam Angle

-  15°
-  24°
-  38°
-  55°

Color Temperature

-  2700K
-  3000K
-  4000K
-  5000K
-  6000K

Finishes

-  Black
-  White
-  Customized